	ick County Contract Number: A Number:
Date:	
To:	Frederick County Division of Public Works Department of Construction Management and Inspection 118 North Market Street Frederick, Maryland 21701
From:	Contractor Name Address City, State Zip
Re:	Project Name:
verified numbers	cation Statement: By this submittal, I hereby represent that I have determined and all field measurements, field construction criteria, materials, dimensions, catalog s and similar data and I have checked and coordinated each item with other applicable d shop drawings and all Contract requirements." Contractor Signature Date
Note 1:	Please denote (highlight, check numbers, or otherwise identify) the materials from the following list that you intend to use on this project.
Note 2:	If you desire to use materials that DO NOT appear in the following list, provide substitution information in accordance with Section 1200 of the General Conditions and Standard Specifications for Water Mains, Sanitary Sewers and Related Structures. Failure to provide complete information will result in delays in the approval process and may affect the project schedule.
Note 3:	This list and all substitution information shall be submitted to the Department of Construction Management and Inspection with the Proposal Package

Frederick County Contract Number:			
MPWA Number:			
•			
SAN	ITARY SEW	FR	
5711	PVC Pipe		
Specification Section: 2570	1 ve ripe		
Standard Details: 1, 2, 3, 5, 201, 202, 203, 204,	205 206 208 209 3	210 212 214 215 217 2	18 219 220 221
223	200, 200, 200, 200, 2	210, 212, 211, 213, 217, 2	10, 217, 220, 221,
Standard: SDR35, ASTM D3034 or ASTM F67	9: SDR26. ASTM D	3034 or ASTM D2241	
Approved Manufacturer/Product	Type	Standard	Size
☐ Diamond Plastics Corp	- J p c	15 000-1000-0	
☐ J-M Manufacturing Co., Inc			
□ National Pipe Co.			
□ North American Pipe			
1		1	
DX	C Coglyatad Fitting		
Specification Section: 2570	C Gasketed Fitting	S	
Standard Details: 115, 203, 214, 216, 218, 220			
Standard Details: 113, 203, 214, 216, 218, 220 Standard: SDR35, ASTM D3034 or ASTM F67	0. CDD26 ACTM D	2024 or ASTM D2241	
			Q:
Approved Manufacturer/Product □ GPK Products, Inc.	Part#	Catalog #	Size
☐ The Harrington Corp. ☐ Multi Fittings Corp.			
□ Plastic Trends, Inc.			
i lastic Helias, Ilic.			
	ast Concrete Manho	les	
Specification Section: 3360			
Standard Details: 201, 202, 203, 223			
Standard: ASTM C478, Type II Cement	T		
Approved Manufacturer/Product	Detail	Size	Other
□ Americast			
Atlantic Concrete Products, Inc.			
☐ Frederick Precast Concrete, Inc.			
C. R. Semler, Inc.			
□ Terre-Hill			
Co	oncrete Grade Rings		
Specification Section: 3360			
Standard Details: 10			
Standard: ASTM C478, Type II Cement. Thicks	ness: Max. 6"; Min. 2	". The top grade ring shou	ıld be 2". Total
height not to exceed 18"	· 		
Approved Manufacturer/Product		Thickness	
□ Americast			
☐ Atlantic Concrete Products, Inc.			
☐ Frederick Precast Concrete, Inc.			
□ C. R. Semler, Inc.			
☐ Prism Precast Products, LLC			

Frederick Co MPWA Nur	ounty Contract Number: _ nber: _		
	Prec	ast Cleanout Blocks	
Specification Se	ection: 2570		
Standard Detai	ls: None, associated details 206, 2	08, 209, 212, 210	
Standard: AST	M C478, Type II Cement.		
Approved	l Manufacturer/Product	Sizes to be used	Configurations
Prism Preca	st Products, LLC		-
☐ Frederick P	recast Concrete, Inc		
☐ Mayer Brot	hers, Inc.		
☐ Atlantic Pre	ecast Products, Inc.		
			•

Manhole Frame and Cover; Lamp Hole Frame and Cover					
Specification Section: 2570					
Standard Details: 8A, 9, 212					
Standard: ASTM A48 Grade 30					
	Use				
Approved Manufacturer/Product	Frederick Co.	Sewer	Water	Private	
☐ East Jordan Iron Works, Inc.					
□ Capitol Foundry of Virginia, Inc.					
Chesapeake Foundries, Inc.					

	Manhole Adapters			
Sp	ecification Section: 2570			
Sta	andard Details: 214, 216, 218			
Sta	Standard:			
	Approved Manufacturer/Product	Supplemental Information		
	Kor-N-Seal® NPC, Inc.			
	A-LOK Products, Inc.			
	Press-Boot® Press-Seal Gasket Corp.			

	Sewer Service Saddles					
Sp	ecification Section: 2570					
Sta	andard Details: 206, 207					
Sta	andard: Only if shown on the plans or approv	ed by the	DUSWM			
	Approved Manufacturer/Product	Size	Type of Pipe	Part/Catalog #	Catalog Cut Incl.	
	Sealtite® The General Engineering Co.					
	Romac Industries, Inc., "CB"TM					

	rederick County Contract Number: APWA Number:			
		Non-Shrink Grout		
Spe	ecification Section: 2570, 4200	ton Shrink Grout		
_	indard Details: 201, 202, 204, 211, 214			
	indard: Type II Cement, Corp of Engineers C	RD-588		
	Approved Manufacturer/Product		ntal Information	
	Thorite® Thoro System Products	•		
	Cem Patch			
	Bu	ıtyl Rubber Sealant		
Spe	ecification Section: 2570			
	ndard Details: 10, 112			
	indard: AASHTO M-198, 3/4" diameter [min.]		
	Approved Manufacturer/Product		ntal Information	
	Kent Seal®			
	Bidco Sealants, Inc.			
	ConSeal Concrete Sealants, Inc	CS-102 [only]		
~		Waterproofing For Manhole	S	
	ecification Section: 2570			
	indard Details: 112, 117	2		
Sta	indard: MIL-C-82052; MIL –P-23236P Class		e , , , ,	7
	Approved Manufacturer/Product	Define manu	facturer to be used	<u>a</u>
ш	Clipper Ship®			
		Iron Pipe – Force Main		
_	ecification Section: 2570, 2550			
	indard Details:			
Sta	ndard: AWWA C151, C111, C104		~•	~
_	Approved Manufacturer/Product	Supplemental Information	Size	Class
–	American Cast Iron Pipe	□ Protecto 401 □ Protecto 401		
	Atlantic States Cast Iron Pipe Co.			
	Griffin Pipe Products Co. U.S. Pipe and Foundry Co.	□ Sewper Coat □ Protecto r 401		
	o.s. Tipe and Foundry Co.	1 Totector 401		
C		p Around Operations		
	ecification Section:	D. W.	- N	
	ndard Details: Shown on plans	□ Yes	□ No	
Sta	andard: As shown on approved plans	Minimum Duna Data	Nar-a-k-a	of Dumes
	Approved Vendors Sun Belt Rentals	Minimum Pump Rate □	Number o	or rumps
	Capital Rentals			
ם	Godwin Pumps			
_	Goawin i umps		J	

Frederick County Contract Number:				
MPWA Number:				
Jac	k-N-Bore Opera	tions		
Specification Section: 2950	K-14-Bore Opera	LIOIIS		
Standard Details: 215				
Standard: Casing – AWWA C-200; PVC pipe	– ASTM D-3034	, SDR35; ASTM	F679, SDR35	
Approved Vendors	Casing			Seals
☐ Advance Products and Systems			□ Models AV	VN &/or ACN
☐ Cascade Waterworks Manufacturing			■ Model CCI	ES
☐ Corrosion Control Products			□ Models S, 0	C, or W
Ad	ditional Sewer It	ems		
Manufacturer & Product		Specification	n & Detail	
		•		
	WATER			
	Ductile Iron Pip	•		
Specification Section: 2550	Ductile Iron Fip	<u>e</u>		
Standard Details: 16, 101, 102, 103, 104, 105, 1	06 120 123			
Standard: AWWA C151, C111, C104; 3"-6" Cl		er Class 52: 24" an	d larger annrove	ed by DUSWM
Approved Manufacturer/Product	Spec Spec	Siz		Class
☐ American Cast Iron Pipe	Брес	SIZ		Ciuss
☐ Atlantic States Cast Iron Pipe Co.				
☐ Griffin Pipe Products Co.				
☐ U.S. Pipe and Foundry Co.				
= e.e. ript and reamary ee.				
n	uctile Iron Fittin	οσε		
Specification Section: 2550	uctile II on Fittin	183		
Standard Details: 102, 103, 104, 105, 107, 118				
Standard: AWWA C153, C111, C104; Class 35	0 or AWWA C11	0 C151: Class 25	0	
Approved Manufacturer/Product	Spec	Size	Class	Туре
□ SIGMA Corporation.	Spee	SIEC	CIMOO	- JPC
☐ Tyler/Union Foundry Co.				
☐ U.S. Pipe and Foundry Co.				
☐ Griffin Pipe Products Co.				
1	I.	l L		l .

Frederick County Contract Number:					
MPWA Number:					
		Valves			
Specification Section: 2550		aives			
Standard Details: 108, 109, 112, 115, 116,	117 119 1	21			
Standard: 2" Resilient seat, open left, thread			silient seat, oper	left, MJ A	AWWA
C509;; 16" and Larger, Butterfly Valve, open					
stainless steel on all valves.					
Approved Manufacturer/Product		Def	ine sizes to be u	ised	
☐ Kennedy Valve					
Mueller Company					
□ M & H Valve Co.					
□ Pratt Valve					
☐ Clow Valve Company					
	Fire	Hydrants			
Specification Section: 2550					
Standard Details: 108, 109, 119					
Standard: 6" MJ inlet, 5-1/4 " valve, 2-2 ½	" and 1-4 $\frac{1}{2}$	2" nozzles with N.S	. threads, $1 \frac{1}{2}$ "	open left p	entagonal
operating nut, painted safety yellow.			1 5		
Approved Manufacturer/Product		Standard	Dewaterin	ig J	Bury depth
American Darling D (2 D					
American Darling B-62-B	ala		1		
☐ Kennedy Valve, Model K81 (Only mod	els				
☐ Kennedy Valve, Model K81 (Only mod allowed in Walkersville)					
 Kennedy Valve, Model K81 (Only mod allowed in Walkersville) Mueller Company, Model A-423 (Only 					
 □ Kennedy Valve, Model K81 (Only mod allowed in Walkersville) □ Mueller Company, Model A-423 (Only allowed in Walkersville) 					
 □ Kennedy Valve, Model K81 (Only mod allowed in Walkersville) □ Mueller Company, Model A-423 (Only allowed in Walkersville) 					
 □ Kennedy Valve, Model K81 (Only mod allowed in Walkersville) □ Mueller Company, Model A-423 (Only allowed in Walkersville) 	models	e and Fittings			
 □ Kennedy Valve, Model K81 (Only mod allowed in Walkersville) □ Mueller Company, Model A-423 (Only allowed in Walkersville) □ Clow Medallion 	models	e and Fittings			
 □ Kennedy Valve, Model K81 (Only mod allowed in Walkersville) □ Mueller Company, Model A-423 (Only allowed in Walkersville) □ Clow Medallion Specification Section: 2550	models	e and Fittings			
□ Kennedy Valve, Model K81 (Only mod allowed in Walkersville) □ Mueller Company, Model A-423 (Only allowed in Walkersville) □ Clow Medallion Specification Section: 2550 Standard Details: 115, 116, 117	models Brass Pip	e and Fittings			
 □ Kennedy Valve, Model K81 (Only mod allowed in Walkersville) □ Mueller Company, Model A-423 (Only allowed in Walkersville) □ Clow Medallion Specification Section: 2550	models Brass Pip		emental Inforn	nation	
□ Kennedy Valve, Model K81 (Only mod allowed in Walkersville) □ Mueller Company, Model A-423 (Only allowed in Walkersville) □ Clow Medallion Specification Section: 2550 Standard Details: 115, 116, 117 Standard: AWWA C800-01, Regular Streng	models Brass Pip		emental Inforn	nation	
□ Kennedy Valve, Model K81 (Only mod allowed in Walkersville) □ Mueller Company, Model A-423 (Only allowed in Walkersville) □ Clow Medallion Specification Section: 2550 Standard Details: 115, 116, 117 Standard: AWWA C800-01, Regular Streng Approved Manufacturer/Product	models Brass Pip		emental Inforn	nation	
□ Kennedy Valve, Model K81 (Only mod allowed in Walkersville) □ Mueller Company, Model A-423 (Only allowed in Walkersville) □ Clow Medallion Specification Section: 2550 Standard Details: 115, 116, 117 Standard: AWWA C800-01, Regular Streng Approved Manufacturer/Product □ Merit Brass Company	models Brass Pip		emental Inforn	nation	
□ Kennedy Valve, Model K81 (Only mod allowed in Walkersville) □ Mueller Company, Model A-423 (Only allowed in Walkersville) □ Clow Medallion Specification Section: 2550 Standard Details: 115, 116, 117 Standard: AWWA C800-01, Regular Streng Approved Manufacturer/Product □ Merit Brass Company □ Trenton Pipe Nipple Co.	Brass Pip			nation	
□ Kennedy Valve, Model K81 (Only mod allowed in Walkersville) □ Mueller Company, Model A-423 (Only allowed in Walkersville) □ Clow Medallion Specification Section: 2550 Standard Details: 115, 116, 117 Standard: AWWA C800-01, Regular Streng Approved Manufacturer/Product □ Merit Brass Company □ Trenton Pipe Nipple Co.	Brass Pip	Suppl		nation	
□ Kennedy Valve, Model K81 (Only mod allowed in Walkersville) □ Mueller Company, Model A-423 (Only allowed in Walkersville) □ Clow Medallion Specification Section: 2550 Standard Details: 115, 116, 117 Standard: AWWA C800-01, Regular Streng Approved Manufacturer/Product □ Merit Brass Company □ Trenton Pipe Nipple Co. Join Specification Section: 2550 Standard Details: 109, 118, 120	Brass Pip	Suppl		nation	
□ Kennedy Valve, Model K81 (Only mod allowed in Walkersville) □ Mueller Company, Model A-423 (Only allowed in Walkersville) □ Clow Medallion Specification Section: 2550 Standard Details: 115, 116, 117 Standard: AWWA C800-01, Regular Streng Approved Manufacturer/Product □ Merit Brass Company □ Trenton Pipe Nipple Co. Join Specification Section: 2550 Standard Details: 109, 118, 120 Standard: 3" – 16", 350 psi; 18" & larger, 2	Brass Pip	Suppl	t	nation	
□ Kennedy Valve, Model K81 (Only mod allowed in Walkersville) □ Mueller Company, Model A-423 (Only allowed in Walkersville) □ Clow Medallion Specification Section: 2550 Standard Details: 115, 116, 117 Standard: AWWA C800-01, Regular Streng Approved Manufacturer/Product □ Merit Brass Company □ Trenton Pipe Nipple Co. Join Specification Section: 2550 Standard Details: 109, 118, 120 Standard: 3" − 16", 350 psi; 18" & larger, 2 Approved Manufacturer/Product	Brass Pip	Suppl t, Mechanical Join Type	Series	nation	Pressure
□ Kennedy Valve, Model K81 (Only mod allowed in Walkersville) □ Mueller Company, Model A-423 (Only allowed in Walkersville) □ Clow Medallion Specification Section: 2550 Standard Details: 115, 116, 117 Standard: AWWA C800-01, Regular Streng Approved Manufacturer/Product □ Merit Brass Company □ Trenton Pipe Nipple Co. Join Specification Section: 2550 Standard Details: 109, 118, 120 Standard: 3" – 16", 350 psi; 18" & larger, 2 Approved Manufacturer/Product □ Ebaa Iron, Inc.	Brass Pip	Suppl t, Mechanical Join Type alug®	Series □ 1100		Pressure
□ Kennedy Valve, Model K81 (Only mod allowed in Walkersville) □ Mueller Company, Model A-423 (Only allowed in Walkersville) □ Clow Medallion Specification Section: 2550 Standard Details: 115, 116, 117 Standard: AWWA C800-01, Regular Streng Approved Manufacturer/Product □ Merit Brass Company □ Trenton Pipe Nipple Co. Join Specification Section: 2550 Standard Details: 109, 118, 120 Standard: 3" − 16", 350 psi; 18" & larger, 2 Approved Manufacturer/Product	Brass Pip	Suppl t, Mechanical Join Type	Series		Pressure

Frederick County Contract Number:	
MPWA Number:	

	Joint Restraint, Push Joint						
Sp	Specification Section: 2550						
Sta	Standard Details:						
Sta	andard: Must be used with the appropriate	e fitti	ings and pipe; Bells to be p	ainte	ed red		
	Approved Manufacturer/Product	Type Sizes Pressure ratin				ure rating	
	American Cast Iron Pipe Co.		Fast Grip Gasket		4"-12"		350 psi
					14"		250 psi
	Griffin Pipe Products Co.		Field Lok_350 Gasket		4"-12"		250 psi
	The Gripper Gasket Co.		Gripper Gasket		3"-16"		350 psi
	U.S. Pipe and Foundry Co.		Field Lok_350 Gasket		4"-12"		250 psi
	Atlantic States Cast Iron Pipe Co.		_Clow Super Lock		6"-36"		_350 psi

Valve Boxes				
Specification Section: 2550				
Standard Details: 108, 112, 114, 116, 117, 119,	122			
Standard: Cast Iron, Screw Type, 5 1/4" shaft, ASTM A48, Grade 30, Bituminous coating; slide or slip type is				
NOT acceptable				
Approved Manufacturer/Product	Number			
☐ Bingham & Taylor	□ 4905 & 4906			
□ Capitol Foundry	□ VB-FRED			
☐ East Jordon Iron Works	□ 8550 Series			
□ SIGMA Corporation	□ VB 261 thru VB 268			
☐ Tyler Pipe / Union Foundry	□ 6850 Series			

	Tapping Sleeve							
Sp	ecification Section: 2550							
Sta	andard Details: 121							
Sta	andard: MJ Ductile Iron, Working Pressure	e, 200 psi unless otherwise not	ed on plans or specifications.					
	Approved Manufacturer/Product	Number	Sizes					
	American Flow Control	□ Series 1004	14" – 36"					
		□ Series 2800	4" – 16"					
	Tyler Pipe		6" – 12"					
	Mueller Company	□ H-615	4" – 24"					
	M&H Valve		6" – 12"					

	Copper Tubing						
Spe	Specification Section: 2550						
Sta	Standard Details: 110, 111						
Sta	andard: Seamless, Type K, Soft, ASTM B88.	No joints allowed between main and meter vault.					
	Approved Manufacturer/Product Define sizes to be used						
	Cambridge Lee Industries, Inc.						
	Mueller Copper Tube Co.						

Frederick County Contract Number: MPWA Number:		
MP WA Number.		
	Corporation Stop	
Specification Section: 2550	corporation stop	
Standard Details: 111A, 113		
Standard: Ball Valve, 300 psi working pressure	Gripper Style. For services lar	ger than one inch the use of tapped
tees is required.		
Approved Manufacturer/Product	Number	Defines sizes to be used
☐ The Ford Meter Box Co.	□ FB600	
	□ FB1000-G	
	□ FB1700-7	
☐ AY McDonald Mfg. Company	□ 4701B	
	□ 4701BT	
	□ 3149B	
☐ Mueller Company	□ B-25008	
	Angle Ball_Valves	
Specification Section: 2550		
Standard Details: 110, 111A, 115, 124		
Standard: Ball Valve, 300 psi working pressure	e, Locking Wing	
Approved Manufacturer/Product	Number	Size

Sp	Specification Section: 2550							
Sta	Standard Details: 110, 111A, 115, 124							
Sta	Standard: Ball Valve, 300 psi working pressure, Locking Wing							
	Approved Manufacturer/Product	Number			Size			
	The Ford Meter Box Co.,		BA91-323W		3/4"			
			BA91-444W		1"			
			BA94-323W-G		3/4"			
			BA94-444W-G		1"			
	AY McDonald Mfg. Company		4602BYT		³ / ₄ ' x ³ / ₄ " x 02			
			4604BY		³ / ₄ " x ³ / ₄ " x 02			
			4604BY		1" x 1" x 04			
	Mueller Company		B-24273		5/8" x 3/4" x 3/4"			
			B-24273		1"			
			B-24278		5/8" x ³ / ₄ " x ³ / ₄ "			
			B-24278		1"			

	Iron Meter Yoke						
Sp	ecification Section: 2550						
Sta	andard Details: 110.1, 110.2, 110.3, 110.4						
Sta	andard:						
	Approved Manufacturer/Product		Number	Size			
	The Ford Meter Box Co.		Y502				
			Y504				
	AY McDonald Mfg. Company		14-2				
			14-4				
	Mueller Company		H-5020				
			H-5040				

	rederick County Contract Number: IPWA Number:				
	Ex	pans	sion Connection		
	ecification Section: 2550				
	ndard Details: 110				
Sta	ndard:	1			
_	Approved Manufacturer/Product		Number		Size
	The Ford Meter Box Co.		EC-23 EC-4		3/4"
	AY McDonald Mfg. Company		14-2EHG		3/4"
			14-4EHG		1"
	Mueller Company		H-14234		³ / ₄ ", 1"
C		Style	Angle Dual Check Valve	2	
	ecification Section: 2550 ndard Details: 110				
	ndard:				
Sta	Approved Manufacturer/Product		Number		Size
	The Ford Meter Box Co.		HHCA94-323-G		Size
_			HHCA91-444		
	Mueller Company		H-14466-A-05		
	AY McDonald Mfg. Company		12W3YQ 33		3/4"
			12W4YQ 44		
	Conne	ctor	Assembly With Plug		
	ecification Section: 2550				
	ndard Details: 110				
Sta	ndard:	1			
_	Approved Manufacturer/Product	_	Number		Size
	The Ford Meter Box Co.		C14-33-G C14-44-G		
			C14-44-G C14-66-G		
			C14-77-G		
	AY McDonald Mfg. Company		4754T		
	Mueller Company,		H-15451		
u .	* **			•	
		Br	anch Pieces		
Spe	ecification Section: 2550				
	ndard Details: 110.2				
Sta	ndard: 1" CTS x Two 3/4" MIP, 71/2" Spacing	g			
	Approved Manufacturer/Product		Number		Size
	The Ford Meter Box Co.		U48-43		
<u> </u>	AY McDonald Mfg. Company		08UTM		
	Mueller Company		H-15363		

	Trederick County Contract Number: MPWA Number:					
	Tandem	Sette	ers for Individual PR	V		
Spe	ecification Section: 2550					
	indard Details: 110.2, 110.3					
	ındard:					
	Approved Manufacturer/Product		Number			Size
	The Ford Meter Box Co.		A-95095			3/4"
			TYA-4-95095-059			1"
	Mueller Company		215B5020-R6A00			
	AY McDonald Mfg. Company		14L2 WDQQ332 X 9	996		
	The state of the s			-	I	
	Praceii	re R	educing Valve (PRV)			
Sne	ecification Section: 2550	i C IX	cutcing varve (114v)			
	andard Details: 110.2, 110.3					
	indard:					
Sta			Number			Size
	Approved Manufacturer/Product CLA-VAL, Automatic Control Valves			D 3/	" …	th two reducing bushings
	CLA-VAL, Automatic Control Valves		□ Model 990			in two reducing bushings
				□ l'		
		oncre	ete Meter Vaults			
	ecification Section: 2550					
	indard Details: 110.1, 110.2, 110.4					
Sta	ndard: CL-1, ASTM C76 and ASTM C141					
	Approved Manufacturer/Product			Sizes to	be t	ısed
	Frederick Precast Corp					
	Mayer Brothers					
	Prism Precast Products					
		Mete	r Vault Covers			
Sne	ecification Section: 2550		7 44410 00 7015			
_	andard Details: 110.1, 110.2, 110.3, 110.4					
	andard: All holes for electronic meter readers	must	he 2" actual dimension	n		
Sta	Approved Manufacturer/Product	Number				
	The Ford Meter Box Co.		A53TP	Ituli		10T
_	The Fold Weter Box Co.	_	A53TTP			10TT, Pit Ring & Lid
			A53HHT, extra heav	v dutv		11T, heavy duty
			EXT-24, Extension R			FL-24 Flange, use with Pit
		_	EAT-24, EXICUSION K	ang		Ring
	AY McDonald Mfg. Company		74M53TP [74M32A7	rD1		74MPR10TTPP
_	AT MCDonaid Wife, Company		74M531P [74M52A] 74M53ATTPP	ırj		74MPR11TP
			74MX24, Extension 1	Dina		74MPR11TTPP
			74MIX24, Extension I	xiiig		/4IVIF
			/4IVIFKIUIF			

Frederick County Contract Number: MPWA Number:		
	2" Custom Meter Setters	
Specification Section: 2550		
Standard Details: 111A	<u> </u>	
Standard: Include ball valve & check valve on	· ·	G.
Approved Manufacturer/Product	Number	Size
☐ The Ford Meter Box Co.	□ VBHH76-15BHC-44-66-G □ VBHH77-15BHC-44-77-G	□ 1 ½" □ 2"
☐ Mueller Company	□ B-2423-2, 15" riser	□ 1 ½"
	□ B-2423-2, 15" riser	□ 2"
☐ AY McDonald Mfg. Company	□ 20B6XXWDQQ666	□ 1-1/2"
	□ 20B7XXWDQQ776	□ 2"
	Note: $XX = meter height 12', 15",$	
	18", 21", 24" and 2"	
I	Large Meter Vaults	
Specification Section: 2550, 3360		
Standard Details: 112, 112-A		
Standard: ASTM C-478; ASTM C-150, type II	ement	
Approved Manufacturer/Product	Size	
□ C.R. Semler, Inc.		
☐ Frederick Precast		
□ Oldcastle Precast		
☐ Smith-Midland, Corp.		
☐ A.C. Miller Concrete Products		
□ Americast		
Larg	e Meter Vault Ladders	
Specification Section: 2550		
Standard Details: 112A		
Standard: Vertical Aluminum ladder with suppo	rt extension	
Approved Manufacturer/Product	Model	
☐ Halliday Aluminum Ladder	☐ Series L1B with Series L1E Safety	Extension
2" Air	Release/Vacuum Valve	
Specification Section: 2550		
Standard Details: 115, Special Provisions		
Standard: 16 inch T-handle required		
Approved Manufacturer/Product	Number	
□ CLA-VAL Automatic Control Valves	□ 362-CAV332	
☐ Crispin-Multiplex Manufacturing Co.	□ UL20	
□ Valmatic Valves	□ VM-22	

Frederick County Contract Number: MPWA Number:						
2" Corners	tion	/ 2" Bronze Angl	e Valve			
Specification Section: 2550	ition	72 Di onze Angr	c vaive			
Standard Details: 115, Special Provisions						
Standard: Use 2" tapped tee, AWWA threads, 2"	bal'	l corporation and 2	" globe val	ve		
Approved Manufacturer/Product				nber		
☐ The Ford Meter Box Co.		FB1600-7				
☐ AY McDonald Mfg. Company		3148B				
☐ Mueller Company		B-20045				
□ Nibco, Inc.		T-311-Y, Angle V	Valve			
	Sei	rvice Saddle				
Specification Section: 2570						
Standard Details:						
Standard: All Bronze Service Saddles						
Approved Manufacturer/Product			Sei	ries		
☐ The Ford Meter Box Co.		101B		□ 202B		
□ Romac Industries, Inc.						
☐ AY McDonald Mfg. Company		3815 (single strap)	□ 3825	(double strap)	
□ Mueller Company		BR1B		□ BR2	В	
				•		
Jac	k-N-	Bore Operations				
Specification Section:		•				
Standard Details: 123						
Standard: Casing – AWWA C-200; DIP pipe –	- AW	WA C-104				
Approved Vendors		Casing Space	rs		End Seals	
☐ Advance Products and Systems		Model SSI		□ Model	s AW &/or AC	
 Cascade Waterworks Manufacturing 		Model CCS				
Corrosion Control Products				□ Model	s S, C, or W	
Ado	litio	nal Water Items				
List Manufacturer		List appr	opriate spe	cification a	nd detail	
\mathbf{G}	rin	der Pumps				
PVC Pressure Pipe						
Specification Section: 2570	•••	1 1 cosuit 1 ipc				
Standard Details:						
Standard: Gasketed, SDR21, PVC 1120, ASTM	D22	41				
Approved Manufacturer/Product		Type	Stan	dard	Size	
□ CertainTeed Corporation		-JF-	~			
□ National Pipe						
			i			

Frederick County Contract Number: MPWA Number:							
PY	VC Pressure Fitting						
Specification Section: 2570							
Standard Details:							
Standard: Gasketed, SDR21, ASTM D2241							
Approved Manufacturer/Product	Part#	Catalog #	Size				
☐ Flo Control, Inc.							
☐ The Harrington Corp.							
<u> </u>	<u>.</u>						
	PVC Pipe						
Specification Section: 2570	•						
Standard Details:							
Standard: Threaded, Schedule 80, ASTM D2464							
Approved Manufacturer/Product	Type	Standard	Size				
North American Pipe Corporation							
□ Diamond Plastics							
		<u> </u>					
p	VC Purple Primer						
Specification Section: 2570	v e i ui pie i i imei						
Standard Details:							
Standard:							
Approved Manufacturer/Product		Series					
☐ United Elchem Industries, Inc.	☐ Uni-Weld 8700						
	PVC Cement						
Specification Section: 2570	1 + 0 00mm						
Standard Details:							
Standard: Solvent Type							
Approved Manufacturer/Product		Series					
☐ United Elchem Industries, Inc.	☐ Uni-Weld 1500						
Grinder Pump							
Specification Section: 2570							
Standard Details:							
Standard: Control panel must be within sight of	the grinder unit.						
Approved Manufacturer/Product		Model					
□ Environmental One Corp.	☐ Model #2010 [sim						
-	□ Model #2014 [dup	lex]					

Frederick County Contract Number: MPWA Number:							
	Brass Fittings						
Specification: 2570							
Standard Details:							
Standard: Threaded							
Approved Manufacturer/Product	Supplementa	al Information					
☐ Lee Brass Company							
☐ Merit Brass Company							
	Swing Check Valve						
Specification: 2570							
Standard Details:							
Standard: PVC							
Approved Manufacturer/Product		/Series					
☐ Flo Control, Inc.	☐ Compression Type, Series 1						
	□ Solvent Weld Type, Series 1	1520					
	Corporation Stop						
Specification: 2570							
Standard Details:							
Standard:							
Approved Manufacturer/Product	Series	Supplemental Information					
☐ The Ford Meter Box Co.	□ Ballcorp, FB1600 Series						
☐ AY McDonald Mfg. Company	☐ Ball Type, No.3148B						
	Curb Box						
Specification: 2570							
Standard Details:							
Standard: Screw Type							
Approved Manufacturer/Product	Supplementa	al Information					
☐ Tyler Pipe (#142R)							
	Detector Tape						
Specification: 2570							
Standard Details:							
Standard: 3 inch wide, Safety Green							
Approved Manufacturer/Product	Supplementa	Supplemental Information					
□ Allen System							
□ Magntec							
Direct Bury Cable							
Specification:	De	tail:					
Specification: 2570							
Standard Details:							
Standard: Type UF, Cable with ground wire, 1							
Approved Manufacturer/Product	Supplementa	al Information					
İ	T T T T T T T T T T T T T T T T T T T						